



TX



RX

## General SPEC:

Frequency Range	2401.92~2479.68 MHz
Channel Selection	8 channels (tact switch)
Antenna Type.	Inverted F
DC Input Port	3.5mm DC Jack
Operating Temperature	-10 ~ 60°C
Storage temperature	- 40 ~ +125°C
Operating Range (LOS)	40meters, typ.
Tx / Rx Pairing	Tact Switch
Power On/Off	Slide Switch

## Transmitter SPEC:

Supply voltage	DC+5V
Supply current	110mA
Modulation Type	GFSK
Transmission Power	8.5±1dBm
Channel Spacing	9MHz (8CH)
Time of Sleeping mode	450hr
Time of Operating	5hr
Dimensions	20mm*34mm*61mm

## Receiver SPEC:

TX Power (dBm, Typ.)	8.0~9.5 dBm (can be any AW digital audio transmitters)
RX Sensitivity (dBm, Max.)	-80 dBm
Channel Frequency (MHz)	2401.9 ~ 2480.9
LOS Transmission Distance	35M Field test with face-to-face TX & RX antennas (M, Min.)
S/N Ratio (dB, Min.) Input=1kHz @ 2Vp-p (20kHz LPF)	80dB
Output Power Rating	Surround L/R 10W*2 (THD=10%) RMS
AC Power Input	220V~230V; 50Hz
Impedance	Surround L/R 4 Ohms

**\*\*For more detail information or products enquiry, please contact :**  
[sales@airwave.com.tw](mailto:sales@airwave.com.tw) or [sales1@airwave.com.tw](mailto:sales1@airwave.com.tw)



**AIRWAVE**

AIRWAVE TECHNOLOGIES INC.  
4F,NO.9 INDUSTRIAL E. 9TH RD.  
SCIENCE-BASED INDUSTRIAL  
PARK TAIWAN R.O.C.

TEL.: 886-3-5778099

FAX : 886-3-5778199

<http://www.airwave.com.tw>

Copyright ©2007  
AIRWAVE Technologies Inc.  
All Rights Reserved.

\*\*All Specification are subject to change without notice.

***Airwave - Wireless Everywhere***