



TX



RX

## General SPEC:

Frequency Range	2401.92~2479.68 MHz
Channel Selection	8 channels (tact switch)
Antenna Type.	Inverted F
DC Input Port	3.5mm DC Jack
Operating Temperature	-10 ~ 60°C
Storage temperature	- 40 ~ +125°C
Operating Range (LOS)	40meters, typ.
Tx / Rx Pairing	Tact Switch
Power On/Off	Slide Switch

## Transmitter SPEC:

Supply voltage	DC+5V
Supply current	110mA
Modulation Type	GFSK
Transmission Power	8.5±1dBm
Channel Spacing	9MHz (8CH)
Time of Sleeping mode	450hr
Time of Operating	5hr
Dimensions	20mm*34mm*61mm

## Receiver SPEC:

Receiving Sensitivity	-88dBm, typ
Power Supply	DC +9V, 300mA
Current Supply	93+-10mA
Audio Output Port	3.5mm Stereo Jack
Audio frequency response	20~20kHz
Audio latency	3.8ms typ.
Tx , Rx pairing ID Code	16 Bit
Auto muting	support
S/N ratio	85dB
Power ON/OFF LED Indicator	Operation : Green OFF : No light
Dimension	W65mm*D16mm*H104mm

**\*\*For more detail information or products enquiry, please contact :  
[sales@airwave.com.tw](mailto:sales@airwave.com.tw) or [sales2@airwave.com.tw](mailto:sales2@airwave.com.tw)**

\*\*All Specification are subject to change without notice.

***Airwave - Wireless Everywhere***



**AIRWAVE**

AIRWAVE TECHNOLOGIES INC.  
4F,NO.9 INDUSTRIAL E. 9TH RD.  
SCIENCE-BASED INDUSTRIAL  
PARK TAIWAN R.O.C.

TEL.: 886-3-5778099  
FAX : 886-3-5778199

<http://www.airwave.com.tw>

Copyright ©2007  
AIRWAVE Technologies Inc.  
All Rights Reserved.