



General SPEC:

| | |
|------------------------|--|
| Frequency Range | 2401.92~2479.68 MHz |
| Channel Selection | 8 channels (tact switch) |
| Channel Spacing | 11MHz |
| Channel Frequency | 2401.920, 2412.288, 2422.656, 2433.024, 2448.576, 2458.944, 2469.312, 2479.680 |
| Frequency stability | + / - 100kHz |
| Modulation | GFSK |
| Antenna Type. | Inverted F |
| TX Power | EIRP + 10dBm |
| Rx Sensitivity | -85dBm (Min.) |
| Audio Output Level | 2.6 Vpp |
| Audio Output Impedance | 16 Ohm (Min.) |
| Audio latency | 3.8ms |
| Response | 20~20kHz, -3dB |
| S/N ratio | 80dB (Min.) |
| THD | 0.7% (Max.) |
| Supply voltage | TX : 9V DC (AWS807T) ; RX : 9V DC (AWS801R) |
| Current consumption | TX : 90 ~ 110mA (Typ.) RX : 89 mA (Typ.) |
| Operating Temperature | -10 ~ 60 °C |
| Operating Range (LOS) | 35meters, typ. |
| Tx / Rx Pairing | Tact Switch |
| Power On/Off | Slide Switch |



AIRWAVE

AIRWAVE TECHNOLOGIES INC.
4F, NO.9 INDUSTRIAL E. 9TH RD.
SCIENCE-BASED INDUSTRIAL
PARK TAIWAN R.O.C.

TEL.: 886-3-5778099
FAX : 886-3-5778199
<http://www.airwave.com.tw>

Copyright ©2007
AIRWAVE Technologies Inc.
All Rights Reserved.

****For more detail information or products enquiry, please contact :**
sales@airwave.com.tw or sales1@airwave.com.tw